

Minivans, Mini SUV'S, Mini Trucks Rules

Brooksville Pulling Association

All cars must be stock unless modifications are stated in the rules. Absolutely no 4x4, if vehicle is 4x4, one drive shaft must be removed.

Any 4 or 6 cylinder allowed, V8 is allowed only if it came factory in vehicle.

No welding anywhere unless specified.

Aftermarket headers, shifters, and pedals are allowed.

Unlimited 9-wire.

Interior

1. 4-point cage and halos are allowed. Must have a minimum of a bar behind bar behind driver's seat. Floating cage only, no down bars.
2. Fuel cell protector can be no bigger than 28"x28", may only be attached to the back seat bar.
3. Transmission coolers are allowed.

Exterior

1. Drivers' door may be welded solid. All other doors allowed unlimited 9-wire or chained.
2. 12"x12" roof sign is required.
3. Body creasing is allowed. Truck beds must remain in the stock up right position.
4. Hood must have a 10"x10" hole cut out.

Suspension

1. Must remain stock. May use 2"x6" flat steel to set ride height. Struts may be welded or clamped.
2. Factory leaf springs only. NO stacked leaves.

Frames, Bumpers, and Core Support

1. Any factory bumper is allowed. May be loaded and seam welded. Homemade bumpers are allowed, pointy bumpers cannot measure more than 10" from the front to the back.
2. 8" bumper shocks may be used to attach bumpers. Maximum thickness of 3/8 and as tall as frame.
3. NO core support spacers.
4. 1" threaded rod through the core support to hold the hood down, threaded rod may replace front subframe mount.
5. May use ¼ 3"x3" 8" long inside frame rail instead of plate on outside of frame.
6. Allowed 6 total repair plates, no bigger than ¼ 4"x6". Must show proof of bend or break.